

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re : Mathieu Gagne and Yuval Ofek  
Serial No. : 10/752,256  
Filed : January 6, 2004  
FOR : METHOD AND APPARATUS FOR CASCADING DATA  
THROUGH REDUNDANT DATA STORAGE UNITS  
EXAMINER : Mark A. Radtke  
ART UNIT : 2165

Commissioner for Patents  
P. O. Box 1450  
Alexandria, VA 22313-1450

DECLARATION OF GEORGE A. HERBSTER

I George A. Herbster state that:

I am a patent attorney (Reg. No. 24,002) registered to  
practice in the United States Patent and Trademark Office;

I am the attorney of record in connection with the above-  
identified patent application.

In that capacity I held initial interviews with Messrs.  
Ofek and Gagne, the named inventors of the above-identified  
application, prepared that application and prosecuted that  
application. I also prepared grandparent application Serial  
No. 09/251,812 filed on February 17, 1999, now U. S. Patent No.  
6,209,002 and the intermediate parent application Serial No.  
09/740,281 filed December 19 2000, now U. S. Patent No.  
6,687,718.

I am submitting this Declaration in support of the Applicants' argument that the claimed invention was made prior to January 6, 1999, the filing date of U. S. Patent No. 6,529,944 to LeCrone for a Host System for Remote Control of Mass Storage Volumes Using Cascading Commands.

During the customary and usual conduct of my practice, I make daily entries into a calendar notebook. Each entry identifies a matter I worked on with a file or docket number, a brief description of the services and the time spent. Monthly my assistant transcribes these notes from my calendar notebook into our Timeslips® time and billing program by Sage Software, Inc. All entries for the grandparent application Serial No. 09/251,812 were entered under my file E30-029.

Exhibit 1 hereto is a report generated by the Timeslips program that identifies my activities in preparing the grandparent application. I have blocked out the monetary amounts associated with each entry. As shown in Exhibit 1, there were a number of activities in connection with the above-identified pending application prior to January 6, 1999, namely:

1. A first conference with Yuval Ofek on September 18, 1998;
2. A second conference with Mathieu Gagne on October 19, 1998;

3. Additional time in November working on a draft application; and
4. The receipt of an EMC confidential document titled "Rules for TimeFinder Operations" from Mathieu Gagne. Exhibit 2 is a copy of that document dated November 12, 1998.

It has been my experience that initial conferences with inventors at EMC Corporation, the assignee of the above-identified patent application, occur only after an invention has been fully conceived.

Exhibit 3 is a letter dated December 1, 1998 sent by me to Mathieu Gagne that includes five sheets of drawings and draft claims for the above-identified patent application. As stated in the second paragraph of Exhibit 3, drawings were included with that letter. Those drawings depicted my understanding of one embodiment of the invention with three different locations and my concept of the differential split implementation of the invention. It is my recollection that these drawings were the basis for FIGS. 2 and 3 of the patent application. Based on my recollection and my usual and customary practice for preparing applications, I would send such drawings only after I felt I had a full understanding of the invention and was seeking verification that my understanding was correct.

The combination of these exhibits, my refreshed recollection and my usual and customary method of preparing

patent applications leads me to conclude that Messrs. Gagne and Ofek had a complete conception of the claimed invention at the time of my initial conferences with them. I also believe that I was diligent in coming to an understanding of the invention and the disclosed embodiment and in the preparation and filing of application Serial No. 09/251,812 on February 17, 1999.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signature:       /George A Herbster/

Typed Name:     GEORGE A. HERBSTER,  
Attorney, Reg. No. 24,002

## EXHIBIT 1

*Law Offices of George A. Herbster*  
Suite 303 Harbors Point  
40 Beach Street  
Manchester, MA 01944

Invoice submitted

April 09, 2007

to:

EMC Corporation

35 Parkwood Drive

Hopkinton MA 01748-9103

Attn: John M. Gunther, Esq.

In Reference SRDF FarPoint Cascading 98-096

To:

File: E30-029

Professional Services

- 9/18/1998 - GAH Conference with Yuval Ofek re patent application
- 10/19/1998 - GAH Conference with Matthew Gagne
- 11/2/1998 - GAH Work re application draft
- 11/3/1998 - GAH Work re application draft
- 11/23/1998 - GAH Work re application draft
- 11/24/1998 - GAH Work re application draft
- 11/30/1998 - GAH Work re application draft
  - GAH Work re application draft and telephone conference with M. Gagne and review new documents
- 12/1/1998 - GAH Work re application draft
- 12/7/1998 - GAH Conference with Matthew Gagne
- 12/11/1998 - GAH Work re application draft -- specification
- 12/14/1998 - GAH Work re application draft
  - GAH Telephone conference and letter to J. Gunther
- 12/28/1998 - GAH Work re application draft
  - GAH Work re application draft
- 12/30/1998 - GAH Conduct a search
- 1/4/1999 - GAH Work re application draft

1/5/1999 - GAH Work re application draft and claims  
- GAH Work re claims  
1/14/1999 - GAH Telephone conference with inventor and work re specification  
1/23/1999 - GAH Work re revisions to specification and drawings  
2/9/1999 - GAH Telephone conference with M. Gagne; revise application and drawings  
2/10/1999 - GAH Telephone conference with M. Gagne re additional revisions  
2/11/1999 - GAH Work re drawings  
- GAH Telephone conference with M. Gagne  
3/29/1999 - GAH Preparation and forwarding of Information Disclosure Statement to USPTO  
4/29/1999 - GAH Preparation and forwarding of missing parts to USPTO  
4/25/2000 - GAH Work re amendment draft  
5/8/2000 - GAH Work re amendment draft  
6/20/2000 - GAH Work re amendment draft  
7/18/2000 - GAH Work re amendment draft  
7/19/2000 - GAH Work re amendment draft  
7/20/2000 - GAH Work re amendment draft  
7/21/2000 - GAH Review and revise amendment  
7/22/2000 - GAH Review and forward draft to client  
8/1/2000 - GAH Telephone conference with M. Gagne; final revisions; forward to USPTO  
10/31/2000 - GAH Review Notice of Allowance; letter to P. Wilson  
11/21/2000 - GAH Work re Rule 312 Amendment  
11/27/2000 - GAH Preparation and forwarding of Issue Fee and formal drawings to USPTO  
1/2/2003 - GAH Review office action; forward to client

For professional services rendered

## EXHIBIT 2



# Rules for TimeFinder operations

Mathieu Gagne  
Code 65 – 11/12/1998  
EMC Confidential

## I. Terminology

---

To describe the TimeFinder operations, we need 2 devices: one called the *standard device* (*STD*), and a *BCV device* (*BCV*). We use the following abbreviations to refer to particular mirror positions of these devices:

SCM	Standard device's configured mirror positions
MMs	Moving mirror's position as a mirror of the standard device
DDF	Differential split tracking session, if it exists
MMb	Moving mirror's position as a mirror of the BCV device
BFM	BCV device's fixed mirrors
m4b	Mirror 4 (tracking mirror) of the BCV device

We will write SCM(|) to signify *any* of the standard device's configured mirror position and SCM(&) to signify *all* of the standard device's configured mirror positions. Similarly for BFM.

We use abbreviations to describe the operations themselves. They consist of 3 letters,  $xyz$ , where:  $x$  is either  $c$  or  $d$  depending on whether the operation is *complete* or *differential*;  $y$  is either  $d$  or  $r$  depending on whether the operation is *direct* or *reverse*; and  $z$  is either  $e$  or  $t$  depending on whether the operation is *establish* or *terminate*. In terms of more familiar terminology, we thus have the following correspondence:

cde	Establish
dde	Re-Establish
cre	Restore
dre	Incremental Restore
cdt	Split
ddt	Differential Split
crt	Reverse Split
drt	Reverse Differential Split.

## II. Rules

---

We present here the rules that govern all 8 TimeFinder operations, that is, the set of axioms to which all TimeFinder behavior can be reduced. These rules *assume* the following bookkeeping is maintained for *every write IO*, at the same time a track is marked to be write pending:

1. Any write to the STD while not established is marked as invalid for MMs and marked as changed for DDF.
2. Any write to the STD while established is marked as changed for DDF.
3. Any write to the BCV is marked as invalid for m4b.
4. Any internal copy to MMs is marked for DDF (new to Code 65, introduced for the purposes of the differential split).

We identify rules new to Code 65 with either a {D} or an {R} depending on whether the rules was introduced for the purposes of the differential split or of the reverse split (of course, the reverse and/or differential split operations were introduced in Code 65). For clarity of presentation, we have divided all the rules into 4 categories, as follows.

### A. HA Reject Conditions

These rules form the first line of defense against possible misuse. The HA receiving the TimeFinder command executes these checks prior to dispatching the request to the DA. The checks consist mainly of verifying that (1) the source of the copy is valid (because TimeFinder operations always involve some copying) and (2) the operation of removing a mirror won't leave invalids stranded (because TimeFinder operations always involve moving a mirror around). Additionally, the establish-type operations (\*\*e) check that write pendings won't get lost.

### B. Write Pendings

These rules indicate what happens to tracks that happen to be write pending to either the BCV or the STD device when the TimeFinder operation is invoked. There is here is fundamental difference between establish-type operations (\*\*e) and terminate-type operations (\*\*t): the former mostly cannot deal with write-pendings and so turn them into invalid tracks (in case they have escaped the detection of the rules in A above), while the latter are prepared to deal with them.

### C. Insure Purpose

These are straightforward rules that make the operation behave like it's supposed to.

### D. Continuity/Persistence/Recovery

These rules insure the proper working of TimeFinder through good times and bad times. *Continuity* refers to the need to manage the data through a chain of TimeFinder operations. *Persistence* means that we're not supposed to lose any data through an IML. And *recovery* covers those cases where rules have been abused (for example, the *force* bit used on a terminate operation) so that there is data loss that we need to keep track of.

### *A. HA Reject Conditions*

#### **1. SCM(&) is invalid**

Motivation: Need source for the copy to the BCV.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12.

#### **2. BCV WP, if revsplitcheck bit is on {R}**

Motivation: We have acknowledged the write to the host, but not destaged it. Upon the establish, we will lose the data. If the next split is a reverse split, we're in trouble.

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

#### **3. BFM(I) is invalid, if revsplitcheck bit is on {R}**

Motivation: If the next split is a reverse split, we do not have the source for the copy.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12.

### *B. Write Pendings*

#### **1. Delete all write pendings to the BCV device, and mark all such as invalid for BFM(&)**

Motivation: In case the next split is a differential split, we need to remember to synchronize this write. Also, in case the next split is a reverse split, in which case we will have lost data; see Ab above.

Microcode: reset\_secondary\_wp, called from hdc\_establish.

### *C. Insure Purpose*

#### **1. Set MMs to invalid**

Motivation: To copy data to the BCV.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

### *D. Continuity/Persistence/Recovery*

#### **1. If BFM(I) is invalid, mark track as changed for DDF {D}**

Motivation: Upon an IML, we would lose the BFM invalid mark, which probably indicates the data hasn't been synced up completely yet. In case the next split is differential, we need to remember this.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

#### **2. If MMb is invalid, set MMs invalid**

Motivation: Need to carry an invalid indication; should not happen because of the HA reject.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

### *A. HA Reject Conditions*

#### **1. SCM(&) is invalid**

Motivation: Need source for the copy to the BCV.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12.

#### **2. BCV WP, if revsplitcheck bit is on {R}**

Motivation: We have acknowledged the write to the host, but not destaged it. Upon the establish, we will lose the data. If the next split is a reverse split, we're in trouble.

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

#### **3. BFM(I) is invalid, if revsplitcheck bit is on {R}**

Motivation: If the next split is a reverse split, we do not have the source for the copy.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12.

### *B. Write Pendings*

#### **1. Delete all write pendings to the BCV device, and mark all such as invalid for BFM(&)**

Motivation: In case the next split is a differential split, we need to remember to synchronize this write. Also, in case the next split is a reverse split, in which case we will have lost data; see Ab above.

Microcode: reset\_secondary\_wp, called from hdc\_establish.

### *C. Insure Purpose*

#### **1. If m4b is invalid, make MMs invalid**

Motivation: To insure a write to the BCV is over-written.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

#### **2. [If MMs is invalid, leave it invalid]**

Motivation: Implicit rule to insure a write to the standard is carried over to the BCV.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

### *D. Continuity/Persistence/Recovery*

#### **1. If BFM(I) is invalid, mark track as changed for DDF {D}**

Motivation: Upon an IML, we would lose the BFM invalid mark, which probably indicates the data hasn't been synced up completely yet. In case the next split is differential, we need to remember this.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

#### **2. If MMb is invalid, set MMs invalid**

Motivation: Need to carry an invalid indication; should not happen because of the HA reject.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

### A. HA Reject Conditions

#### 1. MMb is invalid

Motivation: Need source for the copy to the standard.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12

#### 2. STD is WP

Motivation: To protect the user against itself: it would not make sense to write to a device that's just about to be restored.

Microcode: establish\_bcv\_command, at ebc\_chk\_restore\_wp, after lock.

#### 3. BCV is WP, if revsplitcheck bit is on {R}

Motivation: We have acknowledged the write to the host, but not destaged it. Upon the restore, we will lose the data. If the next split is a reverse split, we're in trouble.

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

#### 4. BFM(I) is invalid, if revsplitcheck bit is on {R}

Motivation: If the next split is a reverse split, we do not have the source for the copy.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

### B. Write Pendings

#### 1. If MMb is WP, carry over cache slot to STD

Motivation: To propagate the write pending to the standard.

Microcode: pyramid: hdc\_establish, at skip\_reset\_wp; cache: update\_invalid\_bits\_for\_bcv\_device at uib\_r\_cyls\_loop, called from hdc\_establish.

#### 2. If BCV is WP, but MMb is not, delete WP, mark track not in cache and mark the slot invalid for BFM(&)

Motivation: The write pending will be propagated to the standard because of the invalidation, so we don't need to keep the WP indication; however, in case of a future reverse split, we need to mark the track invalid.

Microcode: pyramid: hdc\_establish, at skip\_reset\_wp; cache: update\_invalid\_bits\_for\_bcv\_device at uib\_r\_cyls\_loop, called from hdc\_establish.

#### 3. Delete all WP to STD

Motivation: Establish flows can not handle write pendings; this is redundant because of the HA reject, done under lock of the device.

Microcode: reset\_regular\_dv\_wp\_on\_restore (same as reset\_secondary\_wp), called from update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

### C. Insure Purpose

#### 1. Make SCM(&) invalid

Motivation: To copy to the standard device.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

## 2. Make MMs valid

Motivation: Insure source of copy.

Microcode: `update_invalid_bits_for_bcv_device`, called from `hdc_establish`.

### *D. Continuity/Persistence/Recovery*

#### 1. If BFM(I) is invalid, mark track as changed for DDF {D}

Motivation: Upon an IML, we would lose the BFM invalid mark, which probably indicates the data hasn't been synced up completely yet. In case the next split is differential, we need to remember this.

Microcode: `update_invalid_bits_for_bcv_device`, called from `hdc_establish`.

*A. HA Reject Conditions***1. MMb is invalid**

Motivation: Need source for the copy to the standard.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12

**2. STD is WP**

Motivation: To protect the user against itself: it would not make sense to write to a device that's just about to be restored.

Microcode: establish\_bcv\_command, at ebc\_chk\_restore\_wp, after lock.

**3. BCV is WP, if revsplitcheck bit is on {R}**

Motivation: We have acknowledged the write to the host, but not destaged it. Upon the restore, we will lose the data. If the next split is a reverse split, we're in trouble.

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

**4. BFM(I) is invalid, if revsplitcheck bit is on {R}**

Motivation: If the next split is a reverse split, we do not have the source for the copy.

Microcode: get\_invalid\_counts\_establish, called from verify\_parms\_suborder\_12

Microcode: verify\_parms\_suborder\_12, after vps12\_cmd\_ok

*B. Write Pendings***1. If MMb is WP, carry over cache slot to STD**

Motivation: To propagate the write pending to the standard.

Microcode: pyramid: hdc\_establish, at skip\_reset\_wp; cache: update\_invalid\_bits\_for\_bcv\_device at uib\_r\_cyls\_loop, called from hdc\_establish.

**2. If BCV is WP, but MMb is not, delete WP, mark track not in cache and mark the slot invalid for BFM(&)**

Motivation: The write pending will be propagated to the standard because of the invalidation, so we don't need to keep the WP indication; however, in case of a future reverse split, we need to mark the track invalid.

Microcode: pyramid: hdc\_establish, at skip\_reset\_wp; cache: update\_invalid\_bits\_for\_bcv\_device at uib\_r\_cyls\_loop, called from hdc\_establish.

**3. Delete all WP to STD, and mark all such as invalid for SCM(&)**

Motivation: Establish flows can not handle write pendings; this is redundant because of the HA reject, done under lock of the device.

Microcode: reset\_regular\_dv\_wp\_on\_restore (same as reset\_secondary\_wp), called from update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

*C. Insure Purpose***1. If m4b is invalid, mark SCM(&) invalid**

Motivation: So a write to the BCV will be propagated to the standard.

Microcode: update\_invalid\_bits\_for\_bcv\_device, called from hdc\_establish.

## **2. If MMs is invalid, mark SCM(&) invalid**

Motivation: So a write to the standard will be overwritten by the corresponding track on the BCV.

Microcode: `update_invalid_bits_for_bcv_device`, called from `hdc_establish`.

## **3. Set MMs to valid**

Motivation: So the source of the copy exists.

Microcode: `update_invalid_bits_for_bcv_device`, called from `hdc_establish`.

### *D. Continuity/Persistence/Recovery*

## **1. If BFM(I) is invalid, mark track as changed for DDF {D}**

Motivation: Upon an IML, we would lose the BFM invalid mark, which probably indicates the data hasn't been synced up completely yet. In case the next split is differential, we need to remember this.

Microcode: `update_invalid_bits_for_bcv_device`, called from `hdc_establish`.



*A. HA Reject Conditions***1. SCM(&) invalid, unless forced**

Motivation: The standard would be left with a track wholly invalid.

Microcode: `get_invalid_counts_terminate`, called from `verify_parms_suborder_13`

**2. MMs invalid, unless forced**

Motivation: The BCV would end up with a track completely invalid.

Microcode: `get_invalid_counts_terminate`, called from `verify_parms_suborder_13`

**3. WP limit**

Motivation: In case we don't have space to duplicate the cache slots.

Microcode: `get_and_check_regular_device`, called from `verify_parms_suborder_13`

*B. Write Pendings***1. If SCM() and MMs are WP, duplicate cache; watch out for WP limit**

Microcode: `copy_and_update_dv_tables`, at case 2.

**2. If MMs is WP, carry over cache slot to BCV**

Microcode: `copy_and_update_dv_tables`, at case 1.

**3. [If SCM() is WP, leave it be]**

Motivation: To carry a write pending to its destination.

Microcode: `copy_and_update_dv_tables`, at case 3.

*C. Insure Purpose***1. Set BFM(&) to invalid**

Motivation: To initiate a copy to the BCV fixed mirrors from the just split moving mirror.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

**2. Set MMb to valid**

Motivation: It might be that a previous operation left MMb invalid; since the data comes from another device, we can and should forget about the previous invalid state of the MMb.

Microcode: invalid flags are zeroed early in the `copy_and_update_dv_tables` loop.

*D. Continuity/Persistence/Recovery***1. Mark m4b valid**

Motivation: Reset the logging mirror position so we can start keeping track of the writes to the BCV for the next attachment operation.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

## **2. Mark all tracks as unchanged for DDF and delete DDF session**

Motivation: This is the standard way to get rid of the session.

Microcode: manage differential split, called from hdc\_terminate.

## **3. [If MMs is invalid, leave it be]**

Motivation: If we forced a split, we use this to remember the unsynced tracks.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

## **4. If MMs is invalid, set BCV(&) invalid**

Motivation: Carry over the invalid tracks in case of a force.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

### *A. HA Reject Conditions*

#### **1. SCM(&) invalid, unless forced**

Motivation: The standard would be left with a track wholly invalid.

Microcode: `get_invalid_counts_terminate`, called from `verify_parms_suborder_13`

#### **2. MMs invalid, unless forced**

Motivation: The BCV would end up with a track completely invalid.

Microcode: `get_invalid_counts_terminate`, called from `verify_parms_suborder_13`

#### **3. WP limit**

Motivation: In case we don't have space to duplicate the cache slots.

Microcode: `get_and_check_regular_device`, called from `verify_parms_suborder_13`

### *B. Write Pendings*

#### **1. If SCM(!) and MMs are WP, duplicate cache; watch out for WP limit**

Microcode: `copy_and_update_dv_tables`, at case 2.

#### **2. If MMs is WP, carry over cache slot to BCV**

Microcode: `copy_and_update_dv_tables`, at case 1.

#### **3. [If SCM(!) is WP, leave it be]**

Motivation: To carry a write pending to its destination.

Microcode: `copy_and_update_dv_tables`, at case 3.

### *C. Insure Purpose*

#### **1. If DDF is marked changed, set BFM(&) invalid**

Motivation: To insure all changed tracks (and only them) are copied to the fixed mirrors of the BCV.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

#### **2. Set MMb to valid**

Motivation: It might be that a previous operation left MMb invalid; since the data comes from another device, we can and should forget about the previous invalid state of the MMb.

Microcode: invalid flags are zeroed early in the `copy_and_update_dv_tables` loop.

### *D. Continuity/Persistence/Recovery*

#### **1. Mark m4b valid**

Motivation: Reset the logging mirror position so we can start keeping track of the writes to the BCV for the next attachment operation.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

## **2. Mark all tracks as unchanged for DDF**

Motivation: So we can start logging writes to the standard again.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

## **3. [If MMs is invalid, leave it be]**

Motivation: If we forced a split, we use this to remember the unsynced tracks.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

## **4. If MMs is invalid, set BCV(&) invalid**

Motivation: Carry over the invalid tracks in case of a force.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

*A. HA Reject Conditions***1. SCM(&) invalid**

Motivation: The standard would be left with a track wholly invalid.

Microcode: get\_invalid\_counts\_terminate, called from verify\_parms\_suborder\_13

**2. BFM(&) invalid**

Motivation: The BCV would end up with a track completely invalid, which could not be recovered.

Microcode: get\_invalid\_counts\_terminate, called from verify\_parms\_suborder\_13

*B. Write Pendings***1. If SCM() and MMs are WP, delete MMs WP**

Motivation: Since the track will be copied over from the BCV fixed mirrors anyway, there's no need to carry the WP.

Microcode: copy\_and\_update\_dv\_tables, at case 2.

**2. If MMs is WP, delete WP and mark track not in cache**

Motivation: Since the track will be copied over from the BCV fixed mirrors anyway, there's no need to carry the WP.

Microcode: copy\_and\_update\_dv\_tables, at case 1.

**3. [If SCM() is WP, leave it be]**

Motivation: Standard is untouched by operation.

Microcode: copy\_and\_update\_dv\_tables, at case 3.

*C. Insure Purpose***1. Set MMb to invalid**

Motivation: To initiate a copy to the BCV moving mirror from the fixed mirrors.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

*D. Continuity/Persistence/Recovery***1. Set m4b to invalid**

Motivation: In case of a future incremental restore of re-establish, we need to keep track of the fact that the BCV is (possibly) completely out-of-sync with the standard.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

**2. Mark all tracks as unchanged for DDF and delete DDF session**

Motivation: This is the standard way to get rid of the session.

Microcode: manage differential split, called from hdc\_terminate.

### **3. [If BFM(I) is invalid, leave it invalid]**

Motivation: In case an establish was done before the previous sync was finished.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

*A. HA Reject Conditions***1. SCM(&) invalid.**

Motivation: The standard would be left with a track wholly invalid.

Microcode: get\_invalid\_counts\_terminate, called from verify\_parms\_suborder\_13

**2. BFM(&) invalid.**

Motivation: The BCV would end up with a track completely invalid. [This will never get fixed!]

Microcode: get\_invalid\_counts\_terminate, called from verify\_parms\_suborder\_13

*B. Write Pendings***1. If SCM() and MMs are WP, delete MMs WP.**

Motivation: Since the track will be copied over from the BCV fixed mirrors anyway, there's no need to carry the WP.

Microcode: copy\_and\_update\_dv\_tables, at case 2.

**2. If MMs is WP, delete WP and mark track not in cache.**

Motivation: Since the track will be copied over from the BCV fixed mirrors anyway, there's no need to carry the WP.

Microcode: copy\_and\_update\_dv\_tables, at case 1.

**3. [If SCM() is WP, leave it be.]**

Motivation: Standard is untouched by operation.

Microcode: copy\_and\_update\_dv\_tables, at case 3.

*C. Insure Purpose***1. If DDF is marked as changed, set MMb to invalid.**

Motivation: To initiate a copy to the BCV moving mirror from the fixed mirrors, of only those tracks that changed.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

*D. Continuity/Persistence/Recovery***1. [If BFM() is invalid, leave it invalid.]**

Motivation: In case an establish was done before the previous sync was finished.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

**2. If BFM(&) is invalid, set MMb invalid.**

Motivation: If the source of the copy is invalid, we don't have the data.

Microcode: compute\_invalid\_flags\_on\_split, called from copy\_and\_update\_dv\_tables.

### **3. If MMb is invalid, set m4b to invalid.**

Motivation: In case of a future incremental restore or re-establish, we need to keep track of the fact that the BCV track is (possibly) out-of-sync with the standard track.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.

### **4. Mark all tracks as unchanged for DDF.**

Motivation: So we can start logging writes to the standard again.

Microcode: `compute_invalid_flags_on_split`, called from `copy_and_update_dv_tables`.



### III. Checklists

---

For each operation we make certain we have not forgotten anything behind.

cde	Establish
-----	-----------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	-	-	HA reject	-
<b>MMs</b>			-	always
<b>DDF</b>			-	if BFM invalid
<b>MMb</b>	HA reject if rbit;	-	-	-
<b>BFM</b>	make BFM invalid; delete WP	-	HA reject if rbit; mark DDF changed	if BCV WP
<b>m4b</b>			-	-

dde	Re-Establish
-----	--------------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	-	-	HA reject	-
<b>MMs</b>			-	if m4b invalid; if MMb invalid
<b>DDF</b>			-	if BFM invalid
<b>MMb</b>	HA reject if rbit;	-	mark MMs invalid	-
<b>BFM</b>	make BFM invalid; delete WP	-	HA reject if rbit; mark DDF changed	if BCV WP
<b>m4b</b>			make MMs invalid	-

cre	Restore
-----	---------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	HA reject; delete WP	-	-	always
<b>MMs</b>			becomes valid	if MMb invalid
<b>DDF</b>			-	if BFM invalid
<b>MMb</b>	HA reject if rbit;	-	HA reject	-
<b>BFM</b>	make BFM invalid; delete and/or carry WP to STD	-	HA reject if rbit; mark DDF changed; make STD invalid	if BCV WP
<b>m4b</b>			-	-

dre	Incremental Restore
-----	---------------------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	HA reject; mark SCM invalid; delete WP	-	-	if MMs invalid; if m4b invalid; if SCM WP
<b>MMs</b>			make SCM invalid; becomes valid	if MMb invalid
<b>DDF</b>			-	if BFM invalid
<b>MMb</b>	HA reject if rbit;	-	HA reject	-
<b>BFM</b>	make BFM invalid; delete and/or carry WP to STD	-	HA reject if rbit; mark DDF changed; make STD invalid	if BCV WP
<b>m4b</b>			make SCM invalid	-

cdt	Split
-----	-------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	delete and/or carry WP to BCV; see rules.	-	HA reject, unless forced	-
<b>MMs</b>		-	HA reject, unless forced; mark MMb invalid	-
<b>DDF</b>			Mark all unchanged; delete session	
<b>MMb</b>		if MMs is WP	becomes valid	if MMs invalid
<b>BFM</b>			-	always
<b>m4b</b>			becomes valid	-

ddt	Differential Split
-----	--------------------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	delete and/or carry WP to BCV; see rules.	-	HA reject, unless forced	-
<b>MMs</b>		-	HA reject, unless forced; mark MMb invalid	-
<b>DDF</b>			Mark all unchanged	
<b>MMb</b>		if MMs is WP	becomes valid	if MMs invalid
<b>BFM</b>			-	if DDF changed; if MMs invalid
<b>m4b</b>			becomes valid	-

crt	Reverse Split
-----	---------------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	delete or carry WP to BCV; see rules.	-	HA reject, unless forced	-
<b>MMs</b>		-	-	-
<b>DDF</b>			Mark all unchanged; delete session	
<b>MMb</b>		-	-	always
<b>BFM</b>			HA reject, unless forced	-
<b>m4b</b>			-	always

drt	Reverse Differential Split
-----	----------------------------

	<i>if WP</i>	<i>become WP</i>	<i>if invalid</i>	<i>becomes invalid</i>
<b>SCM</b>	delete or carry WP to BCV; see rules.	-	HA reject, unless forced	-
<b>MMs</b>		-	-	-
<b>DDF</b>			Mark all unchanged	
<b>MMb</b>		-	-	if DDF changed; if BFM invalid
<b>BFM</b>			HA reject, unless forced; set MMb invalid	-
<b>m4b</b>			-	if MMb invalid

## IV. Proof

---

We prove a number of facts related to the correct functioning of TimeFinder.

- A. Assume the STD holds dataset A and the BCV holds B. In the absence of IO (write-pending tracks), an establish operation  $\mathcal{x}$  followed by a terminate operation  $\mathcal{y}$  will affect the data in the following way:

$\mathcal{x}$	$\mathcal{y}$	STD	BCV
*de	*dt	A	A
*de	*rt	A	B
*re	*dt	B	B
*re	*rt	B	B

PROOF: ...

- B. Influence of IML...

PROOF: ...

- C. Any write acknowledged to the host will be accounted for...

PROOF: ...

## EXHIBIT 3

LAW OFFICES OF  
GEORGE A. HERBSTER

INTELLECTUAL PROPERTY AND RELATED CAUSES

SUITE 303, HARBOR'S POINT  
40 BEACH STREET  
MANCHESTER, MASSACHUSETTS 01944

TELEPHONE: (978) 526-8111

FACSIMILE: (978) 526-8062  
EMAIL: herbster@star.net

December 1, 1998

Mr. Mattieu Gagne  
EMC Corporation  
171 South Street  
Hopkinton, MA 01748

Re: Patent Application For Far Point Cascading  
EMC File: 98-096  
My File: E30-029

Dear Mattieu,


Enclosed are 5 sheets of drawings and some claims for the far-point cascading patent application.

The three sheets marked 12/19 through 14/19 are drawings from the original BCV application. They show the operation that was presented to the United States Patent and Trademark Office for the "split" and "reestablish" commands. The other two sheets depict my understanding of one embodiment with three different locations. The other depicts my concept of the "differential split" implementation.

The attached claims are drafted to define the crux of the invention. Claims 1 and 6 provide two different approaches. Claims 2 through 5 are "dependent" claims that add steps to the invention as set forth in claim 1.

Please call me after you have a chance to review this material.

Sincerely,



George A. Herbster

GAH:mh

Enclosures  
cc: J. Gunther, Esq.